



SIGNAL TABLE	
PIN NO.	SIGNAL NAME
1	+5V
2	D-
3	D+
4	GND

P/N	DESCRIPTION	GLASS TYPE	DEPTH D
IR6500D25-G0	65" Infrared touchscreen, single-point touch	no glass	12.2mm
IR6500D25-G4	65" Infrared touchscreen, single-point touch	4mm tempered clear glass	16.5mm
IR6500D25-N4	65" Infrared touchscreen, single-point touch	4mm tempered anti-glare glass	16.5mm
IR6500D25-A4	65" Infrared touchscreen, single-point touch	4mm tempered anti-reflective glass	16.5mm
IR6500D25-G0M	65" Infrared touchscreen, multi-touch	no glass	12.2mm
IR6500D25-G4M	65" Infrared touchscreen, multi-touch	4mm tempered clear glass	16.5mm
IR6500D25-N4M	65" Infrared touchscreen, multi-touch	4mm tempered anti-glare glass	16.5mm
IR6500D25-A4M	65" Infrared touchscreen, multi-touch	4mm tempered anti-reflective glass	16.5mm
IR6500D25-G0M7	65" Infrared touchscreen, plug-play multi-touch for Windows 7 only	no glass	12.2mm
IR6500D25-G4M7	65" Infrared touchscreen, plug-play multi-touch for Windows 7 only	4mm tempered clear glass	16.5mm
IR6500D25-N4M7	65" Infrared touchscreen, plug-play multi-touch for Windows 7 only	4mm tempered anti-glare glass	16.5mm
IR6500D25-A4M7	65" Infrared touchscreen, plug-play multi-touch for Windows 7 only	4mm tempered anti-reflective glass	16.5mm

NOTE:
 1.PANEL TAIL CONNECTOR:USB MALE.
 2.FRAME MATERIAL IS ALUMINUM ALLOY.
 3.DEPTH:SEE DETAILS IN RIGHT TABLE FOR VARIOUS P/N

							MODEL	IR6500D25	PROJECTION		
							DESCRIPTION	65" Infrared Touchscreen	SIZE:	A4	
							MATERIAL		WEIGHT:	Kg	
							FINISH		COLOR:	BLACK	
A	FIRST ISSUE	10-01-05	Sara	David	Cloud	DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: .X=±1.0 .XX=±0.5 ANGULAR TOL: ±1°		DRAWING NO.:		SHEET 1 OF 1	REV. A